

View Online at <https://aerobasegroup.com/nsn/5950-00-583-4980>

**Reliability Indicator:**

Not established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

3.375 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

3.000 inches single mounting facility single center group

**Frequency Rating:**

50.0 hertz single component or 60.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Winding Shielding Method:**

Internal shield grounded to inclosure single component

**Body Length:**

Between 4.531 inches and 4.593 inches

**Body Width:**

Between 4.094 inches and 4.156 inches

**Body Height:**

Between 5.407 inches and 5.469 inches

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Threaded stud single group

**Winding Function And Quantity:**

1 primary single component and 3 secondary single component

**Thread Size:**

0.190 inches single group

**Winding Operating Current:**

500.0 milliamperes ac single component 3rd secondary

**Winding Operating Voltage:**

95.00 ac volts single component single primary and 105.00 ac volts single component single primary and 115.00 ac volts single component single primary and 190.00 ac volts single component single primary and 210.00 ac volts single component single primary and 230.00 ac volts single component single primary and 250.00 ac volts single component single primary

**Thread Series Designator:**

Unf single group

**Terminal Type And Quantity:**

21 standoff, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A058b0