# NSN 5950-00-587-4763

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-587-4763

# Reliability Indicator:

Not established

## **Frequency Rating:**

90.0 hertz single component and 150.0 hertz single component

# Input-output Phase Relationship:

Single phase to single phase single component

# Winding Shielding Method:

Internal shield grounded to inclosure and core single component

#### **Body Length:**

1.313 inches

**Body Width:** 

1.313 inches

Body Height:

1.750 inches

#### **Distance Between Mounting Facility Centers:**

1.125 inches single mounting facility single center group

Inclosure Type:

Hermetically sealed

**Mounting Facility Quantity:** 

2 single group

Mounting Method:

Threaded stud single group

# Winding Function And Quantity:

1 primary single component and 1 secondary single component

## Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.138 inches single group

### Winding Operating Current:

600.0 milliamperes ac single component single secondary

### Winding Operating Voltage:

6.00 ac volts single component single secondary

#### **Thread Series Designator:**

Unc single group

### **Terminal Type And Quantity:**

4 solder stud

Shelf Life:

N/a

Unit Of Measure:

---

# Demilitarization:

No

# NSN 5950-00-587-4763

Power Transformer - Page 2 of 2

**Fiig:** A058b0

