

View Online at <https://aerobasegroup.com/nsn/5950-00-591-4327>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.557 inches single mounting facility single center group and 1.567 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.120 inches single mounting facility single center group and 1.130 inches single mounting facility single center group

Frequency Rating:

220.0 hertz single component and 550.0 hertz single component

Input-output Phase Relationship:

Three phase to three phase single component

Transformer Winding Connection Type:

Wye-wye

Body Length:

2.500 inches

Body Width:

1.500 inches

Body Height:

2.281 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thread Size:

0.138 inches single group

Winding Operating Current:

500.0 milliamperes ac single component single secondary

Winding Power Rating:

11.5 volts-amperes single component single secondary

Winding Operating Voltage:

23.00 ac volts single component single secondary

Test Data Document:

83843-956c521 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

7 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0