# NSN 5950-00-593-5665

Power Transformer - Page 1 of 2





# Reliability Indicator:

Not established

### Mounting Slot Width:

0.250 inches single group

### **Frequency Rating:**

480.0 hertz single component

#### Input-output Phase Relationship:

Single phase to single phase single component

#### **Maximum Transformer Power Rating:**

230.0 volt-ampere single component

#### Winding Shielding Method:

Core grounded single component

**Body Length:** 

3.500 inches

Body Width:

# 3.812 inches

**Body Height:** 

4.312 inches

#### **Maximum Operating Temp:**

75.0 degrees celsius

## **Distance Between Mounting Facility Centers:**

1.125 inches single mounting facility single center group

#### Inclosure Type:

Hermetically sealed with oil

#### **Mounting Facility Quantity:**

2 single group

#### **Mounting Method:**

Slot single group

#### Winding Function And Quantity:

1 primary single component and 2 secondary single component

#### Winding Operating Current:

70.0 amperes ac single component 3rd secondary

#### Winding Power Rating:

15.0 watts single component all secondary

#### Winding Operating Voltage:

120.00 ac volts single component all secondary

#### **Special Features:**

Leads copper, shell steel, core silectron

#### **Terminal Type And Quantity:**

8 standoff, threaded stud

#### Shelf Life:

N/a

# NSN 5950-00-593-5665

Power Transformer - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A058b0

