Audio Frequency Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-593-8110

Reliabili	ity Indicator:
Not esta	blished
Center 1	To Center Distance Between Mounting Facilities Parallel To Length
1.594 ind	ches single mounting facility single center group
Center 1	To Center Distance Between Mounting Facilities Parallel To Width:
1.469 ind	ches single mounting facility single center group
mpedar	nce Rating In Ohms:
7180.0	single component all secondary
Frequer	ncy Rating:
30.0 her	tz single component and 300.0 hertz single component
Primary	To Secondary Turn Ratio:
1 to 1 to	6 single component
Body Le	ength:
3.500 ind	ches
Body W	/idth:
2.406 ind	ches
Body He	eight:
2.406 ind	ches
nclosu	re Туре:
Hermetic	cally sealed
Mountin	ng Facility Quantity:
4 single	group
Mountin	ng Method:
Threade	d stud single group
Winding	g Function And Quantity:
2 primar	y single component and 2 secondary single component
Thready	/ Qty Per Inch (tpi):
32 single	e group
Thread 3	Size:
).164 ind	ches single group
Winding	g Operating Current:
5.0 millia	amperes dc single component all primary
Thread 3	Series Designator:
Jnc sing	gle group
Fermina	al Type And Quantity:
10 tab, s	solder lug
Shelf Li	fe:
N/a	
Unit Of	Measure:
-	
Demilita	arization:
No	

NSN 5950-00-593-8110

Audio Frequency Transformer - Page 2 of 2

Fiig: A058b0

