

View Online at <https://aerobasegroup.com/nsn/5950-00-594-0224>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.810 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.750 inches single mounting facility single center group

Mounting Hole Diameter:

0.180 inches single group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure single component

Body Length:

4.680 inches

Body Width:

3.690 inches

Body Height:

5.000 inches

End Application:

4851 tacs, radar system antps43e

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Flange single group and unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

134.0 milliamperes ac single component single secondary

Criticality Code Justification:

Feat

Winding Operating Voltage:

2.83 ac kilovolts single component single secondary and 5.802 ac kilovolts single component single secondary and 5.944 ac kilovolts single component single secondary

Special Features:

Weapon system essential

Terminal Type And Quantity:

9 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0