

View Online at <https://aerobasegroup.com/nsn/5950-00-600-0840>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

4.320 inches single mounting facility single center group and 4.440 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.690 inches single mounting facility single center group and 3.810 inches single mounting facility single center group

Mounting Slot Width:

0.312 inches single group

Frequency Rating:

50.0 hertz single component or 60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

Between 5.190 inches and 5.310 inches

Body Width:

5.000 inches

Body Height:

Between 4.688 inches and 4.812 inches

End Application:

Wsd: generator set, 30 kw, 60 hz, skid-mounted (3id) (mep-005a); generator, 15 kw, diesel, military standard family; maint facility, night sight (nsmf), tam e10227; aircrafts, stratofortress b-52 and b-1b

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Flange single group and slot single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Criticality Code Justification:

Feat

Winding Operating Voltage:

208.00 ac volts single component single primary

Special Features:

Weapon system essential

Terminal Type And Quantity:

5 tab, solder lug and 1 wire lead w/lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0