NSN 5950-00-600-0845

Power Transformer - Page 1 of 1



| View Online at https://aerobasegroup.com/nsn/5950-00-600-0845 |
|---|
| Reliability Indicator: |
| Not established |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 2.500 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 2.000 inches single mounting facility single center group |
| Mounting Slot Width: |
| 0.203 inches single group |
| Frequency Rating: |
| 60.0 hertz single component and 400.0 hertz single component |
| Input-output Phase Relationship: |
| Single phase to single phase single component |
| Body Length: |
| Between 2.990 inches and 3.010 inches |
| Body Width: |
| Between 2.550 inches and 2.570 inches |
| Body Height: |
| Between 2.800 inches and 2.820 inches |
| Inclosure Type: |
| Fully enclosed |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Flange single group and slot single group |
| Winding Function And Quantity: |
| 1 primary single component and 1 secondary single component |
| Winding Operating Current: |
| 500.0 milliamperes ac single component single secondary |
| Winding Operating Voltage: |
| 27.00 ac pounds per hour wet single component single secondary |
| Terminal Type And Quantity: |
| 4 turret |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

No

Fiig:

A058b0