

View Online at <https://aerobasegroup.com/nsn/5950-00-601-6231>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.142 inches single mounting facility single center group and 1.172 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.860 inches single mounting facility single center group and 0.890 inches single mounting facility single center group

Mounting Hole Diameter:

0.170 inches single group and 0.200 inches single group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

Between 1.570 inches and 1.630 inches

Body Width:

Between 1.290 inches and 1.350 inches

Body Height:

Between 1.250 inches and 1.310 inches

Maximum Operating Temp:

130.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

2 single group

Mounting Method:

Flange single group and unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Features Provided:

Color coded terminal

Winding Operating Current:

788.0 milliamperes ac single component single secondary

Winding Operating Voltage:

8.00 ac volts single component all secondary

Terminal Type And Quantity:

8 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0