

View Online at <https://aerobasegroup.com/nsn/5950-00-606-4300>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.485 inches single mounting facility single center group and 2.515 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.985 inches single mounting facility single center group and 2.015 inches single mounting facility single center group

Frequency Rating:

50.0 hertz single component and 400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

Between 3.360 inches and 3.390 inches

Body Width:

Between 3.141 inches and 3.171 inches

Body Height:

Between 4.266 inches and 4.296 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 3 secondary single component

Thread Size:

0.190 inches single group

Winding Operating Current:

600.0 milliamperes ac single component 2nd secondary

Winding Power Rating:

5.4 volts-amperes single component 2nd secondary

Winding Operating Voltage:

100.00 ac millivolts single component 1st secondary and 200.00 ac millivolts single component 1st secondary and 300.00 ac millivolts single component 1st secondary and 400.00 ac millivolts single component 1st secondary and 500.00 ac millivolts single component 1st secondary and 600.00 ac millivolts single component 1st secondary and 700.00 ac millivolts single component 1st secondary and 800.00 ac millivolts single component 1st secondary and 900.00 ac millivolts single component 1st secondary

Thread Series Designator:

Unf single group

Terminal Type And Quantity:

47 solder stud

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fig:

A058b0