## NSN 5950-00-606-7586

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-606-7586

Not established Center To Center Distance Between Mounting Facilities Parallel To Length: 1.500 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 1.100 inches single mounting facility single center group Inductance Type: Fixed Inductance Rating: 120.00 millihernies single component single winding and 550.00 millihernies single component single winding Frequency Rating: 90.0 hertz single component and 840.0 hertz single component Body Length: 1.501 inches Body Width: 1.503 inches Body Height: 1.290 inches Winding Quantity: 1 single component Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Facility Quantity: 4 single group Thready Oty Per Inch (tpl): 40 single group Thready Oty Per Inch (tpl): 40 single group Winding Operating Current: 275.0 milliamperes dc single component single winding Dc Resistance Rating in Ohms: 15.600 single component single winding Thread Series Designator: Unc single group Terminal Type And Quantity: 2 pin Shelf Life: N/a	Doliahility Indicator
Center To Center Distance Between Mounting Facilities Parallel To Length:  1.500 inches single mounting facility single center group  Center To Center Distance Between Mounting Facilities Parallel To Width:  1.100 inches single mounting facility single center group  Inductance Type:  Fixed  Inductance Rating:  120.00 millihenries single component single winding and 550.00 millihenries single component single winding  Frequency Rating:  90.0 hertz single component and 840.0 hertz single component  Body Length:  1.910 inches  Body Width:  1.530 inches  Body Height:  1.290 inches  Winding Quantity:  1 single component  Inclosure Type:  Fully enclosed  Mounting Facility Quantity:  4 single group  Mounting Method:  Threadd hole single group  Thread Size:  0.112 inches single group  Winding Operating Current:  275.0 milliamperes dc single component single winding  Dc Resistance Rating in Ohms:  15.600 single component single winding  Thread Series Designator:  Unc single group  Thread Series Designator:  Unc single group  Thread Series Designator:  Unc single group  Threat Terminal Type And Quantity:  2 pin  Shelf Life:  N/a	Reliability Indicator:
1.500 inches single mounting facility single center group  Center To Center Distance Between Mounting Facilities Parallel To Width: 1.100 inches single mounting facility single center group  Inductance Type: Fixed  Inductance Rating: 120.00 millihenries single component single winding and 550.00 millihenries single component single winding Frequency Rating: 90.0 hertz single component and 840.0 hertz single component  Body Length: 1.510 inches  Body Width: 1.530 inches  Body Height: 1.290 inches  Winding Quantity: 1 single component  Inclosure Type: Fully enclosed  Mounting Facility Quantity: 4 single group  Threadd Role single group  Threadd Qty Per Inch (tpi): 40 single group  Winding Operating Current: 275.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 15.600 single component single winding Thread Series Designator: Unc single group  Threating Type And Quantity: 2 pin  Shelf Life: N/a	
Center To Center Distance Between Mounting Facilities Parallel To Width:  1.100 inches single mounting facility single center group  Inductance Type: Fixed  Inductance Rating:  120.00 millihenries single component single winding and 550.00 millihenries single component single winding  Frequency Rating:  90.0 hertz single component and 840.0 hertz single component  Body Length:  1.910 inches  Body Width:  1.530 inches  Body Height:  1.290 inches  Winding Quantity:  1 single component  Inclosure Type:  Fully enclosed  Mounting Facility Quantity:  4 single group  Mounting Method:  Threadd hole single group  Thready City Per Inch (tpi):  40 single group  Winding Operating Current:  275.0 milliamperes dc single component single winding and 600.0 milliamperes dc single component single winding  Dc Resistance Rating In Ohms:  15.600 single component single winding  Thread Series Designator:  Unc single group  Threatinal Type And Quantity:  2 pin  Shelf Life:  N/a	
1.100 inches single mounting facility single center group Inductance Type: Fixed Inductance Rating: 120.00 millihenries single component single winding and 550.00 millihenries single component single winding Frequency Rating: 90.0 hertz single component and 840.0 hertz single component Body Length: 1.910 inches Body Width: 1.530 inches Body Height: 1.290 inches Winding Quantity: 1 single component Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Threadd hole single group Thready Oty Per Inch (tpi): 40 single group Winding Operating Current: 275.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 15.600 single component single winding Thread Series Designator: Unc single group Terminal Type And Quantity: 2 pin Shelf Life: N/a	
Inductance Type: Fixed Inductance Rating: 120.00 millihenries single component single winding and 550.00 millihenries single component single winding Frequency Rating: 90.0 hertz single component and 840.0 hertz single component Body Length: 1.910 inches Body Width: 1.530 inches Body Height: 1.290 inches Winding Quantity: 1 single component Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Facility Quantity: 40 single group Thready Qty Per Inch (tpi): 40 single group Thready Derating Current: 275.0 milliamperes dc single component single winding and 600.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 15.600 single component single winding Thread Series Designator: Unc single group Terminal Type And Quantity: 2 pin Shelf Life: N/a	
Inductance Rating: 120.00 millihenries single component single winding and 550.00 millihenries single component single winding Frequency Rating: 90.0 hertz single component and 840.0 hertz single component Body Length: 1.910 inches Body Width: 1.530 inches Body Width: 1.530 inches Body Height: 1.290 inches Winding Quantity: 1 single component Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Threaded hole single group Thready Qty Per Inch (tpi): 40 single group Winding Operating Current: 275.0 milliamperes dc single component single winding and 600.0 milliamperes dc single component single winding Dc Resistance Rating in Ohms: 15.600 single component single winding Thread Series Designator: Unc single group Terminal Type And Quantity: 2 pin Shelf Life: N/a	
Inductance Rating:  120.00 millihenries single component single winding and 550.00 millihenries single component single winding  Frequency Rating:  90.0 hertz single component and 840.0 hertz single component  Body Length:  1.910 inches  Body Width:  1.530 inches  Body Height:  1.290 inches  Winding Quantity:  1 single component  Inclosure Type:  Fully enclosed  Mounting Facility Quantity:  4 single group  Threadd hole single group  Threadd y Per Inch (tpl):  40 single group  Thread Size:  0.112 inches single group  Winding Operating Current:  275.0 milliamperes dc single component single winding and 600.0 milliamperes dc single component single winding  Thread Sizes Designator:  Unc single group  Thread Series Designator:  Unc single group  Terminal Type And Quantity:  2 pin  Shelf Life:  N/a	
120.00 millihenries single component single winding and 550.00 millihenries single component single winding Frequency Rating: 90.0 hertz single component and 840.0 hertz single component Body Length: 1.910 inches Body Midth: 1.530 inches Body Height: 1.290 inches Winding Quantity: 1 single component Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Threaded hole single group Thread Size: 0.112 inches single group Winding Operating Current: 275.0 milliamperes dc single component single winding Thread Series Designator: Unc single group Terminal Type And Quantity: 2 pin Shelf Life: N/a	
Frequency Rating: 90.0 hertz single component and 840.0 hertz single component  Body Length: 1.910 inches Body Width: 1.530 inches Body Height: 1.290 inches Winding Quantity: 1.290 inches Winding Quantity: 1 single component Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Threaded hole single group Thready Qty Per Inch (tpi): 40 single group Winding Operating Current: 275.0 milliamperes dc single component single winding and 600.0 milliamperes dc single component single winding De Resistance Rating In Ohms: 15.600 single component single winding Thread Series Designator: Unc single group Terminal Type And Quantity: 2 pin Shelf Life: N/a	·
90.0 hertz single component and 840.0 hertz single component  Body Length: 1.910 inches  Body Width: 1.530 inches  Body Height: 1.290 inches  Winding Quantity: 1 single component Inclosure Type: Fully enclosed  Mounting Facility Quantity: 4 single group  Mounting Method: Threaded hole single group  Thready Qty Per Inch (tpi): 40 single group  Winding Operating Current: 275.0 milliamperes dc single component single winding and 600.0 milliamperes dc single component single winding  De Resistance Rating In Ohms: 15.600 single component single winding  Thread Streis Designator: Unc single group  Terminal Type And Quantity: 2 pin  Shelf Life: N/a	120.00 millihenries single component single winding and 550.00 millihenries single component single winding
Body Length:  1.910 inches  Body Width:  1.530 inches  Body Height:  1.290 inches  Winding Quantity:  1 single component  Inclosure Type: Fully enclosed  Mounting Facility Quantity:  4 single group  Mounting Method: Threaded hole single group  Thread Size:  0.112 inches single group  Winding Operating Current:  275.0 milliamperes dc single component single winding  Dc Resistance Rating In Ohms:  15.600 single component single winding  Thread Series Designator:  Unc single group  Terminal Type And Quantity:  2 pin  Shelf Life:  N/a	Frequency Rating:
1.910 inches  Body Width: 1.530 inches  Body Height: 1.290 inches  Winding Quantity: 1 single component Inclosure Type: Fully enclosed  Mounting Facility Quantity: 4 single group  Mounting Method: Threaded hole single group  Thready Qty Per Inch (tpi): 40 single group  Winding Operating Current: 275.0 milliamperes dc single component single winding and 600.0 milliamperes dc single component single winding  Dc Resistance Rating In Ohms: 15.600 single component single winding  Thread Series Designator: Unc single group  Terminal Type And Quantity: 2 pin  Shelf Life: N/a	90.0 hertz single component and 840.0 hertz single component
Body Width:  1.530 inches  Body Height:  1.290 inches  Winding Quantity:  1 single component Inclosure Type:  Fully enclosed  Mounting Facility Quantity:  4 single group  Mounting Method:  Threaded hole single group  Thready Qty Per Inch (tpi):  40 single group  Thread Size:  0.112 inches single group  Winding Operating Current:  275.0 milliamperes dc single component single winding and 600.0 milliamperes dc single component single winding  Dc Resistance Rating In Ohms:  15.600 single component single winding  Thread Series Designator:  Unc single group  Terminal Type And Quantity:  2 pin  Shelf Life:  N/a	Body Length:
1.530 inches  Body Height: 1.290 inches  Winding Quantity: 1 single component Inclosure Type: Fully enclosed  Mounting Facility Quantity: 4 single group  Mounting Method: Threaded hole single group  Thready Qty Per Inch (tpi): 40 single group  Thread Size: 0.112 inches single group  Winding Operating Current: 275.0 milliamperes dc single component single winding and 600.0 milliamperes dc single component single winding  Dc Resistance Rating In Ohms: 15.600 single component single winding  Thread Series Designator: Unc single group  Terminal Type And Quantity: 2 pin  Shelf Life: N/a	1.910 inches
Body Height:  1.290 inches  Winding Quantity:  1 single component  Inclosure Type:  Fully enclosed  Mounting Facility Quantity:  4 single group  Mounting Method:  Threaded hole single group  Thready Qty Per Inch (tpi):  40 single group  Thread Size:  0.112 inches single group  Winding Operating Current:  275.0 milliamperes dc single component single winding and 600.0 milliamperes dc single component single winding  Dc Resistance Rating In Ohms:  15.600 single component single winding  Thread Series Designator:  Unc single group  Terminal Type And Quantity:  2 pin  Shelf Life:  N/a	Body Width:
1.290 inches Winding Quantity: 1 single component Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Threaded hole single group Thread Size: 0.112 inches single group Winding Operating Current: 275.0 milliamperes dc single component single winding and 600.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 15.600 single component single winding Thread Series Designator: Unc single group Terminal Type And Quantity: 2 pin Shelf Life: N/a	1.530 inches
Winding Quantity:  1 single component  Inclosure Type:  Fully enclosed  Mounting Facility Quantity:  4 single group  Mounting Method:  Threaded hole single group  Thready Qty Per Inch (tpi):  40 single group  Thread Size:  0.112 inches single group  Winding Operating Current:  275.0 milliamperes dc single component single winding and 600.0 milliamperes dc single component single winding  Dc Resistance Rating In Ohms:  15.600 single component single winding  Thread Series Designator:  Unc single group  Terminal Type And Quantity:  2 pin  Shelf Life:  N/a	Body Height:
1 single component Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Threaded hole single group Thready Qty Per Inch (tpi): 40 single group Thread Size: 0.112 inches single group Winding Operating Current: 275.0 milliamperes dc single component single winding and 600.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 15.600 single component single winding Thread Series Designator: Unc single group Terminal Type And Quantity: 2 pin Shelf Life: N/a	1.290 inches
Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Threaded hole single group Thready Qty Per Inch (tpi): 40 single group Thread Size: 0.112 inches single group Winding Operating Current: 275.0 milliamperes dc single component single winding and 600.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 15.600 single component single winding Thread Series Designator: Unc single group Terminal Type And Quantity: 2 pin Shelf Life: N/a	Winding Quantity:
Fully enclosed  Mounting Facility Quantity: 4 single group  Mounting Method: Threaded hole single group  Thready Qty Per Inch (tpi): 40 single group  Thread Size: 0.112 inches single group  Winding Operating Current: 275.0 milliamperes dc single component single winding and 600.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 15.600 single component single winding  Thread Series Designator: Unc single group  Terminal Type And Quantity: 2 pin  Shelf Life: N/a	1 single component
Mounting Facility Quantity: 4 single group  Mounting Method: Threaded hole single group  Thready Qty Per Inch (tpi): 40 single group  Thread Size: 0.112 inches single group  Winding Operating Current: 275.0 milliamperes dc single component single winding and 600.0 milliamperes dc single component single winding  Dc Resistance Rating In Ohms: 15.600 single component single winding  Thread Series Designator: Unc single group  Terminal Type And Quantity: 2 pin  Shelf Life: N/a	Inclosure Type:
4 single group  Mounting Method: Threaded hole single group  Thready Qty Per Inch (tpi): 40 single group  Thread Size: 0.112 inches single group  Winding Operating Current: 275.0 milliamperes dc single component single winding and 600.0 milliamperes dc single component single winding  Dc Resistance Rating In Ohms: 15.600 single component single winding  Thread Series Designator: Unc single group  Terminal Type And Quantity: 2 pin  Shelf Life: N/a	Fully enclosed
Mounting Method: Threaded hole single group Thready Qty Per Inch (tpi): 40 single group Thread Size: 0.112 inches single group Winding Operating Current: 275.0 milliamperes dc single component single winding and 600.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 15.600 single component single winding Thread Series Designator: Unc single group Terminal Type And Quantity: 2 pin Shelf Life: N/a	Mounting Facility Quantity:
Threaded hole single group Thready Qty Per Inch (tpi): 40 single group Thread Size: 0.112 inches single group Winding Operating Current: 275.0 milliamperes dc single component single winding and 600.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 15.600 single component single winding Thread Series Designator: Unc single group Terminal Type And Quantity: 2 pin Shelf Life: N/a	4 single group
Thready Qty Per Inch (tpi): 40 single group Thread Size: 0.112 inches single group Winding Operating Current: 275.0 milliamperes dc single component single winding and 600.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 15.600 single component single winding Thread Series Designator: Unc single group Terminal Type And Quantity: 2 pin Shelf Life: N/a	Mounting Method:
Thread Size:  0.112 inches single group  Winding Operating Current:  275.0 milliamperes dc single component single winding and 600.0 milliamperes dc single component single winding  Dc Resistance Rating In Ohms:  15.600 single component single winding  Thread Series Designator:  Unc single group  Terminal Type And Quantity:  2 pin  Shelf Life:  N/a	Threaded hole single group
Thread Size:  0.112 inches single group  Winding Operating Current:  275.0 milliamperes dc single component single winding and 600.0 milliamperes dc single component single winding  Dc Resistance Rating In Ohms:  15.600 single component single winding  Thread Series Designator:  Unc single group  Terminal Type And Quantity:  2 pin  Shelf Life:  N/a	Thready Qty Per Inch (tpi):
O.112 inches single group  Winding Operating Current:  275.0 milliamperes dc single component single winding and 600.0 milliamperes dc single component single winding  Dc Resistance Rating In Ohms:  15.600 single component single winding  Thread Series Designator:  Unc single group  Terminal Type And Quantity:  2 pin  Shelf Life:  N/a	40 single group
Winding Operating Current:  275.0 milliamperes dc single component single winding and 600.0 milliamperes dc single component single winding  Dc Resistance Rating In Ohms:  15.600 single component single winding  Thread Series Designator:  Unc single group  Terminal Type And Quantity:  2 pin  Shelf Life:  N/a	Thread Size:
275.0 milliamperes dc single component single winding and 600.0 milliamperes dc single component single winding  Dc Resistance Rating In Ohms:  15.600 single component single winding  Thread Series Designator:  Unc single group  Terminal Type And Quantity:  2 pin  Shelf Life:  N/a	0.112 inches single group
Dc Resistance Rating In Ohms:  15.600 single component single winding  Thread Series Designator:  Unc single group  Terminal Type And Quantity:  2 pin  Shelf Life:  N/a	Winding Operating Current:
15.600 single component single winding Thread Series Designator: Unc single group Terminal Type And Quantity: 2 pin Shelf Life: N/a	275.0 milliamperes dc single component single winding and 600.0 milliamperes dc single component single winding
Thread Series Designator: Unc single group Terminal Type And Quantity: 2 pin Shelf Life: N/a	Dc Resistance Rating In Ohms:
Unc single group  Terminal Type And Quantity: 2 pin  Shelf Life: N/a	15.600 single component single winding
Terminal Type And Quantity: 2 pin Shelf Life: N/a	Thread Series Designator:
2 pin Shelf Life: N/a	Unc single group
Shelf Life: N/a	Terminal Type And Quantity:
Shelf Life: N/a	
N/a	
Unit Of Measure:	
Onit Of Measure.	Unit Of Measure:

## NSN 5950-00-606-7586

Reactor - Page 2 of 2



em			

No

Fiig:

A058b0