NSN 5950-00-606-8289

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-606-8289

| Reliability Indicator: |
|--|
| Not established |
| Overall Length: |
| Between 4.063 inches and 4.187 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 3.312 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 2.688 inches single mounting facility single center group |
| Overall Height: |
| 6.437 inches |
| Overall Width: |
| Between 3.438 inches and 3.562 inches |
| Inductance Type: |
| Swinging |
| Inductance Rating: |
| 10.00 henry single component single winding and 20.00 henry single component single winding |
| Frequency Rating: |
| 120.0 hertz single component |
| Body Height: |
| Between 5.438 inches and 5.562 inches |
| Maximum Operating Temp: |
| 65.0 degrees celsius |
| Winding Quantity: |
| 1 single component |
| Inclosure Type: |
| Hermetically sealed |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Unthreaded stud single group |
| Rating Method: |
| Electrical single component single winding |
| Winding Operating Current: |
| 15.0 milliamperes dc single component single winding and 300.0 milliamperes dc single component single winding |
| Dc Resistance Rating In Ohms: |
| 100.000 single component single winding |
| Terminal Type And Quantity: |
| 2 standoff, solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

--

NSN 5950-00-606-8289

Reactor - Page 2 of 2



| em | | | |
|----|--|--|--|
| | | | |
| | | | |

No

Fiig:

A058b0