

View Online at <https://aerobasegroup.com/nsn/5950-00-606-8916>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

6.375 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

4.625 inches single mounting facility single center group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

External inclosure single component

Body Length:

7.375 inches

Body Width:

5.625 inches

Body Height:

8.062 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thready Qty Per Inch (tpi):

20 single group

Thread Size:

0.250 inches single group

Winding Operating Current:

9.0 amperes ac single component single secondary

Winding Operating Voltage:

26.00 ac volts single component single secondary and 31.00 ac volts single component single secondary and 36.00 ac volts single component single secondary and 44.00 ac volts single component single secondary and 51.00 ac volts single component single secondary and 63.00 ac volts single component single secondary and 72.00 ac volts single component single secondary and 80.00 ac volts single component single secondary and 100.00 ac volts single component single secondary and 106.00 ac volts single component single secondary and 115.00 ac volts single component single secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

16 solder stud

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fig:

A058b0