

View Online at <https://aerobasegroup.com/nsn/5950-00-606-8916>

**Reliability Indicator:**

Not established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

6.375 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

4.625 inches single mounting facility single center group

**Frequency Rating:**

60.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Winding Shielding Method:**

External inclosure single component

**Body Length:**

7.375 inches

**Body Width:**

5.625 inches

**Body Height:**

8.062 inches

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Threaded stud single group

**Winding Function And Quantity:**

1 primary single component and 1 secondary single component

**Thready Qty Per Inch (tpi):**

20 single group

**Thread Size:**

0.250 inches single group

**Winding Operating Current:**

9.0 amperes ac single component single secondary

**Winding Operating Voltage:**

26.00 ac volts single component single secondary and 31.00 ac volts single component single secondary and 36.00 ac volts single component single secondary and 44.00 ac volts single component single secondary and 51.00 ac volts single component single secondary and 63.00 ac volts single component single secondary and 72.00 ac volts single component single secondary and 80.00 ac volts single component single secondary and 100.00 ac volts single component single secondary and 106.00 ac volts single component single secondary and 115.00 ac volts single component single secondary

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

16 solder stud

**Shelf Life:**

N/a

**Unit Of Measure:**

**Demilitarization:**

No

**Fiig:**

A058b0