

View Online at <https://aerobasegroup.com/nsn/5950-00-610-0553>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

4.047 inches single mounting facility single center group and 4.077 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.297 inches single mounting facility single center group and 3.327 inches single mounting facility single center group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Core grounded single component and internal shield brought out to terminal single component

Body Length:

Between 4.937 inches and 5.062 inches

Body Width:

Between 3.187 inches and 3.437 inches

Body Height:

Between 5.375 inches and 5.625 inches

Maximum Operating Temp:

105.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thread Size:

0.250 inches single group

Winding Operating Voltage:

9.00 ac volts single component single secondary and 17.00 ac volts single component single secondary and 33.00 ac volts single component single secondary and 41.00 ac volts single component single secondary and 50.00 ac volts single component single secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

10 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0