

View Online at <https://aerobasegroup.com/nsn/5950-00-615-0139>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.580 inches single mounting facility single center group and 0.600 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.580 inches single mounting facility single center group and 0.600 inches single mounting facility single center group

Transformer Function:

Input

Impedance Rating In Ohms:

95000.0 single component single secondary

Frequency Rating:

350.0 hertz single component and 7.0 kilohertz single component

Winding Shielding Method:

Internal shield grounded to inclosure single component

Body Length:

0.750 inches

Body Width:

0.750 inches

Body Height:

1.125 inches

Maximum Operating Temp:

105.0 degrees celsius

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

2 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thread Size:

0.112 inches single group

Winding Operating Current:

3.0 milliamperes dc single component single primary

Special Features:

Case metal material

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

4 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0