

View Online at <https://aerobasegroup.com/nsn/5950-00-615-0356>

Reliability Indicator:

Not established

Overall Length:

5.781 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

4.875 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

4.875 inches single mounting facility single center group

Overall Height:

7.000 inches

Overall Width:

5.781 inches

Frequency Rating:

50.0 hertz single component and 60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

External inclosure single component

Inclosure Type:

Fully enclosed

Mounting Method:

Flange single group

Winding Function And Quantity:

1 primary, fixed autotransformer type single component

Winding Operating Voltage:

25.00 ac pounds per hour wet single component single primary output and 55.00 ac pounds per hour wet single component single primary output and 75.00 ac pounds per hour wet single component single primary output and 95.00 ac pounds per hour wet single component single primary output and 100.00 ac pounds per hour wet single component single primary output and 105.00 ac pounds per hour wet single component single primary output and 110.00 ac pounds per hour wet single component single primary output and 115.00 ac pounds per hour wet single component single primary output and 120.00 ac pounds per hour wet single component single primary output and 125.00 ac pounds per hour wet single component single primary output

Terminal Type And Quantity:

12 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0