

View Online at <https://aerobasegroup.com/nsn/5950-00-615-0413>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.859 inches single mounting facility single center group and 0.891 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.859 inches single mounting facility single center group and 0.891 inches single mounting facility single center group

Overall Height:

Between 1.937 inches and 2.188 inches

Frequency Rating:

380.0 hertz single component and 1.5 kilohertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Maximum Transformer Power Rating:

6.3 volt-ampere single component

Winding Shielding Method:

Internal shield grounded to inclosure single component

Body Length:

Between 1.250 inches and 1.313 inches

Body Width:

Between 1.250 inches and 1.313 inches

Body Height:

Between 1.625 inches and 1.750 inches

Maximum Operating Temp:

105.0 degrees celsius

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

2 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thread Size:

0.138 inches single group

Winding Operating Current:

55.0 milliamperes ac single component single primary

Winding Operating Voltage:

6.30 ac volts single component single secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

5 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0