

View Online at <https://aerobasegroup.com/nsn/5950-00-615-4466>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.000 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.438 inches single mounting facility single center group

Impedance Rating In Ohms:

37.5 single component 1st secondary

Frequency Rating:

60.0 hertz single component

Maximum Transformer Power Rating:

100.0 watts single component

Primary To Secondary Turn Ratio:

9-55/64 to 1 single component

Winding Shielding Method:

Internal shield grounded to core and brought out to terminal single component

Body Length:

3.375 inches

Body Width:

3.000 inches

Body Height:

5.250 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.190 inches single group

Winding Operating Current:

180.0 milliamperes dc single component single primary

Thread Series Designator:

Unf single group

Terminal Type And Quantity:

8 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0