

View Online at <https://aerobasegroup.com/nsn/5950-00-615-4525>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.000 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.625 inches single mounting facility single center group

Frequency Rating:

350.0 hertz single component and 2.0 kilohertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure single component

Body Length:

2.625 inches

Body Width:

2.250 inches

Body Height:

3.000 inches

Maximum Operating Temp:

130.0 degrees celsius

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 10 secondary single component

Thread Size:

0.164 inches single group

Winding Operating Current:

900.0 milliamperes ac single component 4th secondary

Winding Power Rating:

9.0 volts-amperes single component 1st secondary

Winding Operating Voltage:

6.30 ac volts single component all secondary

Special Features:

One primary winding; ten secondary windings

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

23 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0