NSN 5950-00-615-5670

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-615-5670

| Reliability Indicator: |
|---|
| Not established |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 2.375 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 2.062 inches single mounting facility single center group |
| Inductance Type: |
| Fixed |
| Inductance Rating: |
| 4.00 henry single component single winding |
| Body Length: |
| 3.000 inches |
| Body Width: |
| 2.875 inches |
| Body Height: |
| 3.750 inches |
| Winding Quantity: |
| 1 single component |
| Inclosure Type: |
| Fully enclosed |
| Mounting Facility Quantity: |
| 4 single group |
| |
| Mounting Method: |
| Mounting Method: Threaded stud single group |
| - |
| Threaded stud single group |
| Threaded stud single group Rating Method: |
| Threaded stud single group Rating Method: Electrical single component single winding |
| Threaded stud single group Rating Method: Electrical single component single winding Thready Qty Per Inch (tpi): |
| Threaded stud single group Rating Method: Electrical single component single winding Thready Qty Per Inch (tpi): 32 single group |
| Threaded stud single group Rating Method: Electrical single component single winding Thready Qty Per Inch (tpi): 32 single group Thread Size: |
| Threaded stud single group Rating Method: Electrical single component single winding Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.164 inches single group |
| Threaded stud single group Rating Method: Electrical single component single winding Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.164 inches single group Winding Operating Current: |
| Threaded stud single group Rating Method: Electrical single component single winding Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.164 inches single group Winding Operating Current: 270.0 milliamperes dc single component single winding |
| Threaded stud single group Rating Method: Electrical single component single winding Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.164 inches single group Winding Operating Current: 270.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: |
| Threaded stud single group Rating Method: Electrical single component single winding Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.164 inches single group Winding Operating Current: 270.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 85.000 single component single winding |
| Threaded stud single group Rating Method: Electrical single component single winding Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.164 inches single group Winding Operating Current: 270.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 85.000 single component single winding Thread Series Designator: |
| Threaded stud single group Rating Method: Electrical single component single winding Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.164 inches single group Winding Operating Current: 270.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 85.000 single component single winding Thread Series Designator: Unc single group |
| Threaded stud single group Rating Method: Electrical single component single winding Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.164 inches single group Winding Operating Current: 270.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 85.000 single component single winding Thread Series Designator: Unc single group Terminal Type And Quantity: |

--

Unit Of Measure:

NSN 5950-00-615-5670

Reactor - Page 2 of 2



Demilitarization:

No

Fiig:

A058b0