

View Online at <https://aerobasegroup.com/nsn/5950-00-615-5825>

Center To Center Distance Between Mounting Facilities Parallel To Length:

5.000 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

4.625 inches single mounting facility single center group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Maximum Transformer Power Rating:

1.5 kilovolt-ampere single component

Winding Shielding Method:

Internal shield grounded to inclosure single component

Body Length:

7.000 inches

Body Width:

6.375 inches

Body Height:

9.750 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thready Qty Per Inch (tpi):

20 single group

Thread Size:

0.250 inches single group

Winding Operating Current:

50.0 amperes ac single component single secondary

Winding Operating Voltage:

440.00 ac volts single component single primary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

2 standoff, solder lug and 2 standoff, solderless lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0