NSN 5950-00-615-9573

Power Autotransformer Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-615-9573

| View Online at https://aerobasegroup.com/nsn/5950-00-615-9573 |
|---|
| Reliability Indicator: |
| Not established |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 1.490 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 1.440 inches single mounting facility single center group |
| Mounting Hole Diameter: |
| 0.250 inches single group |
| Frequency Rating: |
| 2.0 kilohertz single component and 2.5 kilohertz single component |
| Input-output Phase Relationship: |
| Single phase to single phase single component |
| Body Length: |
| 2.000 inches |
| Body Width: |
| 2.120 inches |
| Body Height: |
| 2.000 inches |
| Inclosure Type: |
| Open |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Flange single group and unthreaded hole single group |
| Winding Function And Quantity: |
| 1 primary, fixed autotransformer type single component |
| Winding Operating Current: |
| 4.5 amperes ac single component single primary output |
| Winding Power Rating: |
| 700.0 volts-amperes single component single primary input |
| Winding Operating Voltage: |
| 115.00 ac volts single component single primary input |
| Terminal Type And Quantity: |
| 8 tab, solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

Fiig:

A058b0