NSN 5950-00-615-9576

Power Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-615-9576

| Reliability Indicator: Not established Center To Center Distance Between Mounting Facilities Parallel To Length: 1.300 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 1.250 inches single mounting facility single center group Frequency Rating: 2.0 kilohertz and 2.5 kilohertz single component Input-output Phase Relationship: Single phase to single phase single component Winding Shielding Method: Internal shield grounded to inclosure single component Body Length: 2.060 inches Body Width: 2.500 inches Inclosure Type: Open |
|--|
| Center To Center Distance Between Mounting Facilities Parallel To Length: 1.300 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 1.250 inches single mounting facility single center group Frequency Rating: 2.0 kilohertz and 2.5 kilohertz single component Input-output Phase Relationship: Single phase to single phase single component Winding Shielding Method: Internal shield grounded to inclosure single component Body Length: 2.060 inches Body Width: 2.750 inches Body Height: 2.500 inches |
| 1.300 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 1.250 inches single mounting facility single center group Frequency Rating: 2.0 kilohertz and 2.5 kilohertz single component Input-output Phase Relationship: Single phase to single phase single component Winding Shielding Method: Internal shield grounded to inclosure single component Body Length: 2.060 inches Body Width: 2.750 inches Body Height: 2.500 inches Dogin ches |
| Center To Center Distance Between Mounting Facilities Parallel To Width: 1.250 inches single mounting facility single center group Frequency Rating: 2.0 kilohertz and 2.5 kilohertz single component Input-output Phase Relationship: Single phase to single phase single component Winding Shielding Method: Internal shield grounded to inclosure single component Body Length: 2.060 inches Body Width: 2.750 inches Body Height: 2.500 inches Inclosure Type: Open |
| 1.250 inches single mounting facility single center group Frequency Rating: 2.0 kilohertz and 2.5 kilohertz single component Input-output Phase Relationship: Single phase to single phase single component Winding Shielding Method: Internal shield grounded to inclosure single component Body Length: 2.060 inches Body Width: 2.750 inches Body Height: 2.500 inches Inclosure Type: Open |
| Frequency Rating: 2.0 kilohertz and 2.5 kilohertz single component Input-output Phase Relationship: Single phase to single phase single component Winding Shielding Method: Internal shield grounded to inclosure single component Body Length: 2.060 inches Body Width: 2.750 inches Body Height: 2.500 inches Inclosure Type: Open |
| 2.0 kilohertz and 2.5 kilohertz single component Input-output Phase Relationship: Single phase to single phase single component Winding Shielding Method: Internal shield grounded to inclosure single component Body Length: 2.060 inches Body Width: 2.750 inches Body Height: 2.500 inches Inclosure Type: Open |
| Input-output Phase Relationship: Single phase to single phase single component Winding Shielding Method: Internal shield grounded to inclosure single component Body Length: 2.060 inches Body Width: 2.750 inches Body Height: 2.500 inches Inclosure Type: Open |
| Single phase to single phase single component Winding Shielding Method: Internal shield grounded to inclosure single component Body Length: 2.060 inches Body Width: 2.750 inches Body Height: 2.500 inches Inclosure Type: Open |
| Winding Shielding Method: Internal shield grounded to inclosure single component Body Length: 2.060 inches Body Width: 2.750 inches Body Height: 2.500 inches Inclosure Type: Open |
| Internal shield grounded to inclosure single component Body Length: 2.060 inches Body Width: 2.750 inches Body Height: 2.500 inches Inclosure Type: Open |
| Body Length:2.060 inchesBody Width:2.750 inchesBody Height:2.500 inchesInclosure Type:Open |
| 2.060 inches Body Width: 2.750 inches Body Height: 2.500 inches Inclosure Type: Open |
| Body Width: 2.750 inches Body Height: 2.500 inches Inclosure Type: Open |
| 2.750 inches Body Height: 2.500 inches Inclosure Type: Open |
| Body Height: 2.500 inches Inclosure Type: Open |
| 2.500 inches Inclosure Type: Open |
| Inclosure Type: Open |
| Open |
| |
| Mounting Eacility Quantity: |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Flange and unthreaded hole single group |
| Winding Function And Quantity: |
| 1 primary and 1 secondary single component |
| Winding Operating Current: |
| 5.0 amperes ac single component single secondary |
| Winding Operating Voltage: |
| 60.00 ac volts single component single secondary |
| Terminal Type And Quantity: |
| 6 tab, solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A058b0 |
| |