## NSN 5950-00-617-3512

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-617-3512

Reliability Indicator:
Not established
Center To Center Distance Between Mounting Facilities Parallel To Length:
4.000 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Width:
3.000 inches single mounting facility single center group
Inductance Type:
Swinging
Inductance Rating:
20.00 millihenries single component single winding and 40.00 millihenries single component single winding
Body Length:
5.062 inches
Body Width:
3.000 inches
Body Height:
5.000 inches
Winding Quantity:
1 single component
Inclosure Type:
Hermetically sealed
Mounting Facility Quantity:
4 single group
Mounting Method:
Threaded stud single group
Rating Method:
Electrical single component single winding
Thready Qty Per Inch (tpi):
32 single group
Thread Size:
0.138 inches single group
Winding Operating Current:
5.0 amperes dc single component single winding and 10.0 amperes dc single component single winding
Dc Resistance Rating In Ohms:
0.750 single component single winding
Thread Series Designator:
Unc single group
Terminal Type And Quantity:
2 standoff insulator
Shelf Life:
N/a
Unit Of Measure:

--

## NSN 5950-00-617-3512

Reactor - Page 2 of 2



_		••	• •				
וו	em	ш	112	rız	211	n	٠.

No

Fiig:

A058b0