

View Online at <https://aerobasegroup.com/nsn/5950-00-617-4028>

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.625 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.750 inches single mounting facility single center group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core single component

Body Length:

2.688 inches

Body Width:

2.312 inches

Body Height:

2.438 inches

Inclosure Type:

Open

Mounting Facility Quantity:

4 single group

Mounting Method:

Flange single group and unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 10 secondary single component

Special Features:

Eprimary winding 115 v rating, secondary windings rated 6.4 v at 9 amp, 10 v at 100 ua, 10 v at 100 ua, 10 v 100 ua, 10 at 100 ua, 10 v at 100 ua, 10 v at 100 ua, 26 v at 250 ma, 185 v at 60 ma, 185 v at 60 ma

Terminal Type And Quantity:

22 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0