NSN 5950-00-617-4103

Saturable Reactor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-617-4103

| Overall Length: |
|---|
| 2.062 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 1.500 inches all mounting facilities all center groupings |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 1.500 inches all mounting facilities all center groupings |
| Overall Height: |
| 2.062 inches |
| Overall Width: |
| 2.688 inches |
| Frequency Rating: |
| 415.0 hertz all components |
| Mounting Facility Quantity: |
| 4 all groupings |
| Mounting Method: |
| Threaded hole all groupings |
| Winding Function And Quantity: |
| 12 primary and 1 control all components |
| Thready Qty Per Inch (tpi): |
| 40 all groupings |
| Thread Size: |
| 0.112 inches all groupings |
| Dc Resistance Rating In Ohms: |
| 400.000 single component 1st control |
| Winding Operating Voltage: |
| 80.00 ac volts single component all primary |
| Thread Series Designator: |
| Unc all groupings |
| Terminal Type And Quantity: |
| 6 tab, solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A058b0 |
| |