

View Online at <https://aerobasegroup.com/nsn/5950-00-617-4135>

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.625 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.750 inches single mounting facility single center group

Mounting Hole Diameter:

0.188 inches single group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core single component

Body Length:

2.688 inches

Body Width:

2.312 inches

Body Height:

2.438 inches

Inclosure Type:

Open

Mounting Facility Quantity:

4 single group

Mounting Method:

Flange single group and unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 10 secondary single component

Special Features:

Primary winding 115 v rating, secondary windings rated 6.4 v at 11.5 amp, 10 v at 1 ma, 10 v at 1 ma, 10 v at 1 ma, 10 v at 1 ma, 10 v at 1 ma, 26 v at 250 ma, 600 v at 70 ma w/center tap, 600 v at 75 ma w/center tap

Terminal Type And Quantity:

24 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0