

View Online at <https://aerobasegroup.com/nsn/5950-00-617-4135>

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.625 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

0.750 inches single mounting facility single center group

**Mounting Hole Diameter:**

0.188 inches single group

**Frequency Rating:**

400.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Winding Shielding Method:**

Internal shield grounded to core single component

**Body Length:**

2.688 inches

**Body Width:**

2.312 inches

**Body Height:**

2.438 inches

**Inclosure Type:**

Open

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Flange single group and unthreaded hole single group

**Winding Function And Quantity:**

1 primary single component and 10 secondary single component

**Special Features:**

Primary winding 115 v rating, secondary windings rated 6.4 v at 11.5 amp, 10 v at 1 ma, 10 v at 1 ma, 10 v at 1 ma, 10 v at 1 ma, 10 v at 1 ma, 26 v at 250 ma, 600 v at 70 ma w/center tap, 600 v at 75 ma w/center tap

**Terminal Type And Quantity:**

24 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0