

View Online at <https://aerobasegroup.com/nsn/5950-00-617-4932>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.000 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.688 inches single mounting facility single center group

Impedance Rating In Ohms:

100.0 single component 2nd secondary

Frequency Rating:

30.0 hertz single component and 20.0 kilohertz single component

Maximum Transformer Power Rating:

100.0 watts single component

Primary To Secondary Turn Ratio:

5-3/4 to 1 to 1 single component

Winding Shielding Method:

Internal shield grounded to inclosure and core single component

Body Length:

4.625 inches

Body Width:

3.875 inches

Body Height:

5.938 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.138 inches single group

Winding Operating Current:

150.0 milliamperes dc single component single primary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

10 standoff, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0