## NSN 5950-00-617-5298

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-617-5298 **Reliability Indicator:** Not established **Mounting Hole Diameter:** 0.312 inches single group Frequency Rating: 400.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component **Winding Shielding Method:** Internal shield grounded to inclosure single component **Body Length:** 1.906 inches **Body Width:** 1.593 inches **Body Height:** 1.750 inches **Maximum Operating Temp:** 100.0 degrees celsius **Distance Between Mounting Facility Centers:** 1.250 inches single mounting facility single center group **Inclosure Type:** Open **Mounting Facility Quantity:** 2 single group **Mounting Method:** Flange single group and unthreaded hole single group Winding Function And Quantity: 1 primary single component and 1 secondary single component **Features Provided:** Color coded lead and tinned wire leads **Winding Operating Current:** 27.0 milliamperes ac single component single primary Winding Operating Voltage: 21.00 ac volts single component 1st secondary and 26.00 ac volts single component 1st secondary and 30.00 ac volts single component 1st secondary and 34.00 ac volts single component 1st secondary and 115.00 ac volts single component 1st secondary **Terminal Type And Quantity:** 8 wire lead Shelf Life: N/a **Unit Of Measure:** 

No

Demilitarization:

## NSN 5950-00-617-5298

Power Transformer - Page 2 of 2



Fiig:

A058b0