

View Online at <https://aerobasegroup.com/nsn/5950-00-617-8777>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

5.750 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.250 inches single mounting facility single center group

Frequency Rating:

387.0 hertz single component and 443.0 hertz single component

Input-output Phase Relationship:

Three phase to three phase single component

Maximum Transformer Power Rating:

2.9 kilovolt-ampere single component

Winding Shielding Method:

Internal shield grounded to core and brought out to terminal single component

Body Length:

8.250 inches

Body Width:

4.750 inches

Body Height:

7.062 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thread Qty Per Inch (tpi):

18 single group

Thread Size:

0.312 inches single group

Winding Operating Current:

14.5 amperes ac single component single secondary

Winding Operating Voltage:

440.00 ac volts single component single primary

Thread Series Designator:

Unc single group

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0