

View Online at <https://aerobasegroup.com/nsn/5950-00-617-8829>

Reliability Indicator:

Not established

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

1.594 inches

Body Width:

1.750 inches

Body Height:

1.875 inches

Distance Between Mounting Facility Centers:

1.250 inches single mounting facility single center group

Inclosure Type:

Open

Mounting Facility Quantity:

2 single group

Mounting Method:

Flange single group and unthreaded hole single group

Winding Function And Quantity:

1 primary, fixed autotransformer type single component

Winding Tap Location (non-core):

Multiple taps w/o center tap single component single primary output

Winding Operating Current:

850.0 milliamperes ac single component single primary output and 120.0 milliamperes ac single component single primary output and 400.0 milliamperes ac single component single primary output and 220.0 milliamperes ac single component single primary output and 300.0 milliamperes ac single component single primary output

Winding Operating Voltage:

18.00 ac pounds per hour wet single component single primary output and 21.00 ac pounds per hour wet single component single primary output and 26.00 ac pounds per hour wet single component single primary output and 34.00 ac pounds per hour wet single component single primary output and 60.00 ac pounds per hour wet single component single primary output

Terminal Type And Quantity:

8 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0