

View Online at <https://aerobasegroup.com/nsn/5950-00-620-5819>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.250 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.375 inches single mounting facility single center group

Mounting Slot Width:

0.188 inches single group

Frequency Rating:

50.0 hertz single component and 400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

2.875 inches

Body Width:

2.625 inches

Body Height:

3.375 inches

Inclosure Type:

Partially enclosed, double shell

Mounting Facility Quantity:

4 single group

Mounting Method:

Flange single group and slot single group

Winding Function And Quantity:

2 primary single component and 2 secondary single component

Winding Operating Current:

4.0 amperes ac single component 3rd secondary

Winding Power Rating:

97.2 volts-amperes single component all secondary

Winding Operating Voltage:

12.00 ac volts single component all secondary and 29.30 ac volts single component all secondary

Special Features:

First and second primary winding taps used to select different secondary voltages

Terminal Type And Quantity:

11 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0