## NSN 5950-00-620-7844

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-620-7844

## **Reliability Indicator:**

Not established

## Center To Center Distance Between Mounting Facilities Parallel To Length:

3.740 inches single mounting facility single center group and 3.760 inches single mounting facility single center group

#### **Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.990 inches single mounting facility single center group and 3.010 inches single mounting facility single center group

#### **Overall Width:**

Between 3.720 inches and 3.780 inches

#### **Mounting Hole Diameter:**

0.200 inches single group and 0.210 inches single group

#### Frequency Rating:

400.0 hertz single component

#### Input-output Phase Relationship:

Three phase to three phase single component

#### **Transformer Winding Connection Type:**

Wye-delta and wye-wye

#### **Body Length:**

5.800 inches

#### **Body Height:**

2.750 inches

## **Maximum Operating Temp:**

210.0 degrees celsius

#### **Inclosure Type:**

Open

## **Mounting Facility Quantity:**

4 single group

## **Mounting Method:**

Unthreaded hole single group

#### Winding Function And Quantity:

1 primary single component and 2 secondary single component

## Winding Operating Current:

42.0 amperes ac single component all secondary

#### **Winding Operating Voltage:**

195.00 ac volts single component single primary and 210.00 ac volts single component single primary

#### **Test Data Document:**

97151-69c37506 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

## **Terminal Type And Quantity:**

10 wire lead

## Shelf Life:

N/a

### **Unit Of Measure:**

--

# NSN 5950-00-620-7844

Power Transformer - Page 2 of 2



Demilitarization:

No

Fiig:

A058b0