

View Online at <https://aerobasegroup.com/nsn/5950-00-625-9692>

Reliability Indicator:

Not established

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

3.750 inches

Body Outside Diameter:

2.050 inches

Inclosure Type:

Hermetically sealed

Mounting Method:

Threaded bushing single group

Winding Function And Quantity:

1 primary, fixed autotransformer type single component

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.375 inches single group

Winding Operating Current:

3.0 amperes ac single component single primary output and 3.3 amperes ac single component single primary output and 3.6 amperes ac single component single primary output and 3.9 amperes ac single component single primary output and 4.2 amperes ac single component single primary output and 4.5 amperes ac single component single primary output and 4.8 amperes ac single component single primary output and 5.1 amperes ac single component single primary output and 5.6 amperes ac single component single primary output and 6.0 amperes ac single component single primary output

Winding Operating Voltage:

9.00 ac volts single component single primary output and 10.20 ac volts single component single primary output and 11.50 ac volts single component single primary output and 12.80 ac volts single component single primary output and 14.50 ac volts single component single primary output and 16.20 ac volts single component single primary output and 18.50 ac volts single component single primary output and 20.80 ac volts single component single primary output and 24.30 ac volts single component single primary output and 27.80 ac volts single component single primary output

Thread Series Designator:

Unef single group

Terminal Type And Quantity:

12 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0