NSN 5950-00-626-9449

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-626-9449

Reliability Indicator: Not established Frequency Rating: 400.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component Winding Shielding Method: Internal shield brought out to terminal single component Body Length: 0.590 inches Body Outside Diameter: 1.500 inches Installation For Which Designed: Inclosure Type: Fully enclosed Mounting Facility Quantity: 1 single group Mounting Method: Thread hole single group Cooling Method: 1 primary single component and 3 secondary single component Thready Qty Per Inch (tpi): 40 single group
Frequency Rating: 400.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component Winding Shielding Method: Internal shield brought out to terminal single component Body Length: 0.590 inches Body Unside Diameter: 1.500 inches Internal For Which Designed: Indoor nonportable Inclosure Type: Fully enclosed Mounting Facility Quantity: 1 single group Mounting Method: Cooling Method: Threaded hole single group Mounting facility Quantity: 1 primary single component and 3 secondary single component Thready Quy Per Inch (tpi): 4 single group
40.0 herz single component Input-output Phase Relationship: Single phase to single phase single component Winding Shielding Method: Internal shield brought out to terminal single component Body Length: 0.590 inches Body Uutside Diameter: 1.500 inches Installation For Which Designed: Indoor nonportable Inclosure Type: Fully enclosed Mounting Facility Quantity: 1 single group Mounting Method: Threaded hole single group Self-cooled Winding Function And Quantity: 1 primary single component and 3 secondary single component Thready Qty Per Inch (tpi): 40 single group
Input-output Phase Relationship: Single phase to single phase single component Winding Shielding Method: Internal shield brought out to terminal single component Body Length: 0.590 inches Body Outside Diameter: 1.500 inches Installation For Which Designed: Indoor nonportable Inclosure Type: Fully enclosed Mounting Facility Quantity: 1 single group Cooling Method: Self-cooled Winding Function And Quantity: 1 primary single component and 3 secondary single component Thready Qty Per Inch (tpi): 40 single group
Single phase to single phase single component Winding Shielding Method: Internal shield brought out to terminal single component Body Length: 0.590 inches Body Outside Diameter: 1.500 inches Installation For Which Designed: Indoor nonportable Inclosure Type: Fully enclosed Mounting Facility Quantity: 1 single group Mounting Method: Cooling Method: Self-cooled Winding Function And Quantity: 1 primary single component and 3 secondary single component Thready Qty Per Inch (tpi): 40 single group
Winding Shielding Method: Internal shield brought out to terminal single component Body Length: 0.590 inches Body Outside Diameter: 1.500 inches Installation For Which Designed: Indoor nonportable Inclosure Type: Fully enclosed Mounting Facility Quantity: 1 single group Mounting Method: Threaded hole single group Self-cooled Winding Function And Quantity: 1 primary single component and 3 secondary single component Thready Qty Per Inch (tpi): 40 single group
Internal shield brought out to terminal single component Body Length: 0.590 inches Body Outside Diameter: 1.500 inches Installation For Which Designed: Indoor nonportable Indoor nonportable Inclosure Type: Fully enclosed Mounting Facility Quantity: 1 single group Mounting Method: Self-cooled Vinding Function And Quantity: 1 primary single component and 3 secondary single component Thready Qty Per Inch (tpi): 40 single group
Body Length:0.590 inchesBody Outside Diameter:1.500 inchesInstallation For Which Designed:Installation For Which Designed:Indoor nonportableInclosure Type:Fully enclosedMounting Facility Quantity:1 single groupMounting Method:Threaded hole single groupCooling Method:Self-cooledWinding Function And Quantity:1 primary single component and 3 secondary single componentThready Qty Per Inch (tpi):40 single group
0.590 inches Body Outside Diameter: 1.500 inches Installation For Which Designed: Indoor nonportable Inclosure Type: Fully enclosed Mounting Facility Quantity: 1 single group Mounting Method: 1 hreaded hole single group Cooling Method: Self-cooled Winding Function And Quantity: 1 primary single component and 3 secondary single component Thready Qty Per Inch (tpi): 40 single group
Body Outside Diameter:1.500 inchesInstallation For Which Designed:Indoor nonportableInclosure Type:Fully enclosedMounting Facility Quantity:1 single groupMounting Method:Threaded hole single groupCooling Method:Self-cooledWinding Function And Quantity:1 primary single component and 3 secondary single componentThready Qty Per Inch (tpi):40 single group
1.500 inches Installation For Which Designed: Indoor nonportable Indoor nonportable Inclosure Type: Fully enclosed Mounting Facility Quantity: 1 single group Mounting Method: Threaded hole single group Cooling Method: Self-cooled Vinding Function And Quantity: 1 primary single component and 3 secondary single component Thready Qty Per Inch (tpi): 40 single group
Installation For Which Designed: Indoor nonportable Inclosure Type: Fully enclosed Mounting Facility Quantity: 1 single group 1 single group Mounting Method: Threaded hole single group Cooling Method: Self-cooled Winding Function And Quantity: 1 primary single component and 3 secondary single component Thready Qty Per Inch (tpi): 40 single group
Indoor nonportable Inclosure Type: Fully enclosed Mounting Facility Quantity: 1 single group Mounting Method: Threaded hole single group Cooling Method: Self-cooled Winding Function And Quantity: 1 primary single component and 3 secondary single component Thready Qty Per Inch (tpi): 40 single group
Inclosure Type: Fully enclosed Mounting Facility Quantity: 1 single group Mounting Method: Threaded hole single group Cooling Method: Self-cooled Winding Function And Quantity: 1 primary single component and 3 secondary single component Thready Qty Per Inch (tpi): 40 single group
Fully enclosed Mounting Facility Quantity: 1 single group Mounting Method: Threaded hole single group Cooling Method: Self-cooled Winding Function And Quantity: 1 primary single component and 3 secondary single component Thready Qty Per Inch (tpi): 40 single group
Mounting Facility Quantity:1 single groupMounting Method:Threaded hole single groupCooling Method:Self-cooledWinding Function And Quantity:1 primary single component and 3 secondary single componentThready Qty Per Inch (tpi):40 single group
1 single group Mounting Method: Threaded hole single group Cooling Method: Self-cooled Winding Function And Quantity: 1 primary single component and 3 secondary single component Thready Qty Per Inch (tpi): 40 single group
Mounting Method: Threaded hole single group Cooling Method: Self-cooled Winding Function And Quantity: 1 primary single component and 3 secondary single component Thready Qty Per Inch (tpi): 40 single group
Threaded hole single group Cooling Method: Self-cooled Winding Function And Quantity: 1 primary single component and 3 secondary single component Thready Qty Per Inch (tpi): 40 single group
Cooling Method: Self-cooled Winding Function And Quantity: 1 primary single component and 3 secondary single component Thready Qty Per Inch (tpi): 40 single group
Self-cooled Winding Function And Quantity: 1 primary single component and 3 secondary single component Thready Qty Per Inch (tpi): 40 single group
Winding Function And Quantity: 1 primary single component and 3 secondary single component Thready Qty Per Inch (tpi): 40 single group
1 primary single component and 3 secondary single component Thready Qty Per Inch (tpi): 40 single group
Thready Qty Per Inch (tpi): 40 single group
40 single group
Thread Size:
0.112 inches single group
Winding Operating Current:
45.0 milliamperes ac single component 2nd secondary and 75.0 milliamperes ac single component 2nd secondary
Winding Operating Voltage:
36.00 ac volts single component 1st secondary
Thread Series Designator:
Thread Series Designator: Unc single group
-
Unc single group
Unc single group Terminal Type And Quantity:
Unc single group Terminal Type And Quantity: 11 pin
Unc single group Terminal Type And Quantity: 11 pin Shelf Life:
Unc single group Terminal Type And Quantity: 11 pin Shelf Life: N/a
Unc single group Terminal Type And Quantity: 11 pin Shelf Life: N/a

NSN 5950-00-626-9449

Power Transformer - Page 2 of 2

Fiig: A058b0

