# NSN 5950-00-628-2014

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-628-2014

# Reliability Indicator:

Not established

# Center To Center Distance Between Mounting Facilities Parallel To Length:

2.297 inches single mounting facility single center group

# Center To Center Distance Between Mounting Facilities Parallel To Width:

1.859 inches single mounting facility single center group

#### **Frequency Rating:**

400.0 hertz single component

#### Input-output Phase Relationship:

Three phase to three phase single component

#### Transformer Winding Connection Type:

Delta-delta

**Body Length:** 

3.062 inches

Body Width:

# 2.625 inches

Body Height:

4.250 inches

# Maximum Operating Temp:

130.0 degrees celsius

# Inclosure Type:

Hermetically sealed

#### **Mounting Facility Quantity:**

4 single group

#### **Mounting Method:**

Threaded stud single group

#### Winding Function And Quantity:

1 primary single component and 1 secondary single component

#### **Thread Size:**

0.190 inches single group

#### Winding Operating Current:

2.3 amperes ac single component single secondary

#### Winding Power Rating:

250.0 volts-amperes single component single secondary

#### Winding Operating Voltage:

200.00 ac volts single component single primary

# **Thread Series Designator:**

Unf single group

### **Terminal Type And Quantity:**

6 standoff, threaded stud

#### Shelf Life:

N/a

# NSN 5950-00-628-2014

Power Transformer - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

Yes - demil/mli

Fiig:

A058b0

