

View Online at <https://aerobasegroup.com/nsn/5950-00-630-5889>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.438 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.000 inches single mounting facility single center group

Frequency Rating:

60.0 hertz single component and 180.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

4.125 inches

Body Width:

2.000 inches

Body Height:

3.500 inches

Inclosure Type:

Open

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thready Qty Per Inch (tpi):

28 single group

Thread Size:

0.250 inches single group

Winding Operating Current:

6.0 milliamperes ac single component single secondary

Winding Operating Voltage:

8.50 ac kilovolts single component single secondary

Thread Series Designator:

Unf single group

Terminal Type And Quantity:

5 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0