NSN 5950-00-630-6887

Power Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-630-6887

| Deliability Indicator |
|--|
| Reliability Indicator: |
| Not established |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 3.250 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 3.000 inches single mounting facility single center group |
| Mounting Slot Width: |
| 0.188 inches single group |
| Frequency Rating: |
| 50.0 hertz single component and 60.0 hertz single component |
| Input-output Phase Relationship: |
| Single phase to single phase single component |
| Winding Shielding Method: |
| Internal shield grounded to inclosure and brought out to terminal single component |
| Body Length: |
| 4.500 inches |
| Body Width: |
| 3.750 inches |
| Body Height: |
| 4.000 inches |
| End Application: |
| Forrestal class cv |
| Inclosure Type: |
| Partially enclosed, double shell |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Flange single group and slot single group |
| Winding Function And Quantity: |
| 2 primary single component and 5 secondary single component |
| Terminal Type And Quantity: |
| 16 wire lead |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A058b0 |