NSN 5950-00-631-9701

Potential Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-631-9701

Reliability Indicator:
Not established
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.375 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Width:
0.812 inches single mounting facility single center group
Frequency Rating:
380.0 hertz single component and 420.0 hertz single component
Body Length:
2.281 inches
Body Width:
1.094 inches
Body Height:
2.000 inches
Installation For Which Designed:
Indoor nonportable
Inclosure Type:
Fully enclosed
Mounting Facility Quantity:
4 single group
Mounting Method:
Threaded hole single group
Winding Function And Quantity:
1 primary single component and 1 secondary single component
Thready Qty Per Inch (tpi):
Thready Qty Per Inch (tpi): 32 single group
32 single group
32 single group Thread Size:
32 single group Thread Size: 0.138 inches single group
32 single group Thread Size: 0.138 inches single group Winding Operating Voltage:
32 single group Thread Size: 0.138 inches single group Winding Operating Voltage: 115.00 ac volts single component single primary and 200.00 ac volts single component single primary
32 single group Thread Size: 0.138 inches single group Winding Operating Voltage: 115.00 ac volts single component single primary and 200.00 ac volts single component single primary Terminal Type And Quantity:
32 single group Thread Size: 0.138 inches single group Winding Operating Voltage: 115.00 ac volts single component single primary and 200.00 ac volts single component single primary Terminal Type And Quantity: 4 tab, solder lug
32 single group Thread Size: 0.138 inches single group Winding Operating Voltage: 115.00 ac volts single component single primary and 200.00 ac volts single component single primary Terminal Type And Quantity: 4 tab, solder lug Shelf Life:
32 single group Thread Size: 0.138 inches single group Winding Operating Voltage: 115.00 ac volts single component single primary and 200.00 ac volts single component single primary Terminal Type And Quantity: 4 tab, solder lug Shelf Life: N/a
32 single group Thread Size: 0.138 inches single group Winding Operating Voltage: 115.00 ac volts single component single primary and 200.00 ac volts single component single primary Terminal Type And Quantity: 4 tab, solder lug Shelf Life: N/a
Thread Size: 0.138 inches single group Winding Operating Voltage: 115.00 ac volts single component single primary and 200.00 ac volts single component single primary Terminal Type And Quantity: 4 tab, solder lug Shelf Life: N/a Unit Of Measure:
Thread Size: 0.138 inches single group Winding Operating Voltage: 115.00 ac volts single component single primary and 200.00 ac volts single component single primary Terminal Type And Quantity: 4 tab, solder lug Shelf Life: N/a Unit Of Measure: Demilitarization: