## NSN 5950-00-635-4957

Power Transformer - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5950-00-635-4957             |
|---|
| Reliability Indicator:  |
| Not established   |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 4.000 inches single mounting facility single center group                 |
| Center To Center Distance Between Mounting Facilities Parallel To Width:  |
| 3.000 inches single mounting facility single center group                 |
| Mounting Hole Diameter:   |
| 0.312 inches single group   |
| Frequency Rating:   |
| 60.0 hertz single component   |
| Input-output Phase Relationship:  |
| Single phase to single phase single component                             |
| Maximum Transformer Power Rating:   |
| 250.0 volt-ampere single component  |
| Body Length:  |
| 5.750 inches  |
| Body Width:   |
| 3.750 inches  |
| Body Height:  |
| 7.500 inches  |
| Inclosure Type:   |
| Fully enclosed  |
| Mounting Facility Quantity:   |
| 4 single group  |
| Mounting Method:  |
| Flange single group and unthreaded hole single group                      |
| Cooling Type:   |
| Fins  |
| Cooling Method:   |
| Self-cooled   |
| Winding Function And Quantity:  |
| 1 primary single component and 1 secondary single component               |
| Winding Operating Voltage:  |
| 440.00 ac volts single component single primary                           |
| Terminal Type And Quantity:   |
| 6 tab, solder lug   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |

No

Demilitarization:

## NSN 5950-00-635-4957

Power Transformer - Page 2 of 2



Fiig:

A058b0