NSN 5950-00-645-0229

Power Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-645-0229

| Reliability Indicator: |
|--|
| Not established |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 3.875 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 2.438 inches single mounting facility single center group |
| Overall Height: |
| 5.938 inches |
| Frequency Rating: |
| 350.0 hertz single component and 450.0 hertz single component |
| Input-output Phase Relationship: |
| Single phase to single phase single component |
| Body Length: |
| 4.469 inches |
| Body Width: |
| 2.969 inches |
| Body Height: |
| 5.500 inches |
| Inclosure Type: |
| Hermetically sealed |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Unthreaded stud single group |
| Winding Function And Quantity: |
| 1 primary single component and 3 secondary single component |
| Winding Operating Current: |
| 300.0 milliamperes ac single component 3rd secondary |
| Winding Operating Voltage: |
| 90.00 ac volts single component 1st secondary and 300.00 ac volts single component 1st secondary and 700.00 ac volts single componen |
| 1st secondary and 910.00 ac volts single component 1st secondary and 1.00 ac kilovolts single component 1st secondary |
| Terminal Type And Quantity: |
| 13 tab, solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A058b0 |