NSN 5950-00-645-0543

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-645-0543

Reliabili	ty Indicator:
Not esta	blished
Center 1	o Center Distance Between Mounting Facilities Parallel To Length:
3.438 ind	ches single mounting facility single center group
Center 1	o Center Distance Between Mounting Facilities Parallel To Width:
4.250 ind	ches single mounting facility single center group
Frequen	cy Rating:
50.0 her	tz single component and 1.0 kilohertz single component
Input-ou	Itput Phase Relationship:
Single pl	nase to single phase single component
Winding	Shielding Method:
Internal	shield grounded to inclosure single component
Body Le	ength:
5.500 ind	ches
Body W	idth:
4.500 inc	ches
Body He	eight:
6.000 ind	ches
Inclosur	е Туре:
Hermetic	cally sealed
Mountin	g Facility Quantity:
4 single	group
Mountin	g Method:
Threade	d stud single group
Winding	Function And Quantity:
1 primar	y single component and 4 secondary single component
Thready	Qty Per Inch (tpi):
32 single	group
Thread \$	Size:
0.138 ind	ches single group
-	Operating Current:
70.0 mill	iamperes ac single component 2nd secondary
-	Operating Voltage:
	c volts single component 3rd secondary
	Series Designator:
	le group
	I Type And Quantity:
	off insulator
Shelf Lif	ie:
N/a	
Unit Of I	Measure:

NSN 5950-00-645-0543

Power Transformer - Page 2 of 2

Demilitarization:

No

Fiig:

A058b0

