

View Online at <https://aerobasegroup.com/nsn/5950-00-645-0623>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

6.000 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.125 inches single mounting facility single center group and 2.125 inches single mounting facility single center group

Mounting Hole Diameter:

0.250 inches single group

Frequency Rating:

50.0 hertz single component and 60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure single component

Body Length:

6.120 inches

Body Width:

5.265 inches

Body Height:

7.125 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

6 single group

Mounting Method:

Unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

212.0 milliamperes ac single component single secondary

Winding Operating Voltage:

210.00 ac volts single component single primary and 220.00 ac volts single component single primary and 230.00 ac volts single component single primary and 240.00 ac volts single component single primary and 250.00 ac volts single component single primary

Terminal Type And Quantity:

9 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0