

View Online at <https://aerobasegroup.com/nsn/5950-00-645-0630>

Reliability Indicator:

Not established

Overall Length:

4.375 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.500 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.750 inches single mounting facility single center group

Overall Height:

3.875 inches

Overall Width:

4.312 inches

Mounting Slot Width:

0.219 inches single group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core and mounting single component

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Flange single group and slot single group

Winding Function And Quantity:

1 primary single component and 5 secondary single component

Winding Operating Current:

5.0 milliamperes ac single component 4th secondary

Winding Operating Voltage:

6.30 ac volts single component 1st secondary

Special Features:

5 secondary windings; secondary winding 5, 2.55 v center tap

Terminal Type And Quantity:

14 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0