

View Online at <https://aerobasegroup.com/nsn/5950-00-645-0702>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.500 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.375 inches single mounting facility single center group

Transformer Function:

Input

Impedance Rating In Ohms:

100.0 single component single primary

Frequency Rating:

200.0 hertz single component and 4.0 kilohertz single component

Maximum Transformer Power Rating:

60.0 milliwatts single component

Primary To Secondary Turn Ratio:

1 to 22-1/2 single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

2.125 inches

Body Width:

2.000 inches

Body Height:

2.688 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.138 inches single group

Winding Operating Current:

80.0 milliamperes dc single component single primary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

5 standoff, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0