

View Online at <https://aerobasegroup.com/nsn/5950-00-645-0734>

**Reliability Indicator:**

Not established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.500 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

1.375 inches single mounting facility single center group

**Impedance Rating In Ohms:**

12000.0 single component 1st secondary

**Frequency Rating:**

200.0 hertz single component and 4.0 kilohertz single component

**Maximum Transformer Power Rating:**

2.0 watts single component

**Primary To Secondary Turn Ratio:**

1 to 7-1/3 to 75 single component

**Winding Shielding Method:**

Internal shield brought out to terminal single component

**Body Length:**

2.188 inches

**Body Width:**

2.000 inches

**Body Height:**

3.000 inches

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Threaded stud single group

**Winding Function And Quantity:**

1 primary single component and 2 secondary single component

**Thready Qty Per Inch (tpi):**

32 single group

**Thread Size:**

0.138 inches single group

**Winding Operating Current:**

10.0 milliamperes dc single component single primary

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

8 standoff, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0