NSN 5950-00-645-1061

Power Transformer - Page 1 of 2

Reliability Indicator:

Frequency Rating:

60.0 hertz single component

Not established



View Online at https://aerobasegroup.com/nsn/5950-00-645-1061

2.250 inches single mounting facility single center group

2.375 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Length:

Center To Center Distance Between Mounting Facilities Parallel To Width:

| Input-output Phase Relationship: |
|---|
| Single phase to single phase single component |
| Winding Shielding Method: |
| Internal shield grounded to inclosure single component |
| Body Length: |
| 3.250 inches |
| Body Width: |
| 3.000 inches |
| Body Height: |
| 4.125 inches |
| Maximum Operating Temp: |
| 65.0 degrees celsius |
| Inclosure Type: |
| Fully enclosed |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Threaded stud single group |
| Winding Function And Quantity: |
| 1 primary single component and 2 secondary single component |
| Thread Size: |
| 0.138 inches single group |
| Winding Operating Current: |
| 70.0 milliamperes ac single component 1st secondary |
| Winding Operating Voltage: |
| 6.30 ac volts single component 2nd secondary |
| Thread Series Designator: |
| Unc single group |
| Terminal Type And Quantity: |
| 6 solder stud |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |

NSN 5950-00-645-1061

Power Transformer - Page 2 of 2



Demilitarization:

No

Fiig:

A058b0