

| NSN 5950-00-645-1355 Reactor - Page 1 of 2 | G |
|---|---|
| View Online at https://aerobasegroup.com/nsn/5950-00-645-1355 | |
| Reliability Indicator: | |
| Not established | |
| Center To Center Distance Between Mounting Facilities Parallel To Length: | |
| 2.688 inches single mounting facility single center group | |
| Center To Center Distance Between Mounting Facilities Parallel To Width: | |
| 2.688 inches single mounting facility single center group | |
| Overall Height: | |
| 7.750 inches | |
| Inductance Type: | |
| Fixed | |
| Inductance Rating: | |
| 3.00 henry single component all winding | |
| Body Length: | |
| 3.312 inches | |
| Body Width: | |
| 3.312 inches | |
| Body Height: | |
| 6.938 inches | |
| Maximum Operating Temp: | |
| 65.0 degrees celsius | |
| Winding Quantity: | |
| 2 single component | |
| Inclosure Type: | |
| Hermetically sealed | |
| | |

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Rating Method:

Electrical single component all winding

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.190 inches single group

Winding Operating Current:

500.0 milliamperes dc single component 2nd winding

Dc Resistance Rating In Ohms:

47.500 single component 1st winding

Thread Series Designator:

Unf single group

Terminal Type And Quantity:

4 standoff, solder lug

NSN 5950-00-645-1355

Reactor - Page 2 of 2



| | Life: |
|--|-------|
| | |
| | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0